

**WEST**[Help](#)[Logout](#)[Interrupt](#)[Main Menu](#)[Search Form](#)[Posting Counts](#)[Show S Numbers](#)[Edit S Numbers](#)[Preferences](#)[Cases](#)**Search Results -**

Terms	Documents
L5 and (al2O3 or siO2)	45

**Database:**

[US Patents Full-Text Database](#)  
[US Pre-Grant Publication Full-Text Database](#)  
[JPO Abstracts Database](#)  
[EPO Abstracts Database](#)  
[Derwent World Patents Index](#)  
[IBM Technical Disclosure Bulletins](#)

**Search:**

L7

[Refine Search](#)[Recall Text](#)[Clear](#)**Search History**
**DATE: Monday, April 28, 2003**    [Printable Copy](#)    [Create Case](#)
**Set Name   Query**

side by side

**Hit Count   Set Name**

result set

*DB=PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=OR*

<u>L7</u>	L5 and (al2O3 or siO2)	45	<u>L7</u>
<u>L6</u>	L5 and (al2o3 or siO2)	45	<u>L6</u>
<u>L5</u>	L4 and (oxide adj3 inclusion) or (inclusion adj3 oxide)	555	<u>L5</u>
<u>L4</u>	(chromium or cr or cr:) and (nickel or ni or ni:) and (carbon or c or c:) and (silicon or si or si:) and (manganese or mn or mn:)	32748	<u>L4</u>

*DB=USPT; PLUR=YES; OP=OR*

<u>L3</u>	L2 and (chromium or cr or cr:) and (nickel or ni or ni:) and (carbon or c or c:) and (silicon or si or si:) and (manganese or mn or mn:)	151	<u>L3</u>
<u>L2</u>	L1 and inclusion	163	<u>L2</u>
<u>L1</u>	(148/325)!.CCLS. or 148/327.ccls. or 420/34.ccls. or 420/45.ccls. or 420/58.ccls. or 420/91.ccls.	1071	<u>L1</u>

**WEST**

Generate Collection

Print

L2: Entry 43 of 60.

File: JPAB

May 28, 1993

PUB-NO: JP405132740A

DOCUMENT-IDENTIFIER: JP 05132740 A

TITLE: PRODUCTION OF HOT-DIP GALVANIZED STEEL SHEET FOR DEEP DRAWING EXCELLENT IN  
PITTING CORROSION RESISTANCE

PUBN-DATE: May 28, 1993

## INVENTOR-INFORMATION:

NAME

COUNTRY

HAMANAKA, SEIICHI

FUJIWARA, SUSUMU

MUNESHITA, MIKIO

YAMADA, TOSHIRO

INT-CL (IPC): C22C 38/00; C22C 38/54; C23C 2/02; C23C 2/06; C25D 3/20; C25D 5/26

## ABSTRACT:

PURPOSE: To produce a hot-dip galvanized steel sheet for deep drawing improved in deep drawability and pitting corrosion resistance.

CONSTITUTION: A slab of a steel having a composition consisting of, by weight, &le;0.02% C, &le;1.5% Si, 0.05-1.8% Mn, 0.03-0.20% P, &le;0.015% S, 0.05-1.5% Cu, 0.005-0.100% solAl, &le;0.005% N, 0.005-0.15% Ti, further one or &le;2 kinds among 0.005-0.15% Nb, &le;1% Ni, &le;3% Mo, and &le;7% Cr, and the balance iron with inevitable impurities is hot-rolled, pickled, and cold-rolled. Subsequently, the resulting steel sheet is annealed at 700-950°C and galvanized by means of a continuous hot-dip galvanizing line or is iron-plated by means of a continuous electroplating line and then annealed at 700-950°C and galvanized by means of a continuous hot-dip galvanizing line.

COPYRIGHT: (C)1993,JP0&amp;Japio